



MATERIALS:
 INSULATOR: PA6T, UL94V-0
 CONTACTS: BRASS OR PHOSPHOR BRONZE,
 GOLD FLASH OVER NICKEL

ELECTRICAL:
 CURRENT RATING: 1AMP
 INSULATION RESISTANCE: 1000MΩ MIN.
 DIELECTRIC WITHSTANDING: 500V AC
 OPERATING TEMPERATURE: -55℃~+105℃

注:
 铜针针长16.5mm, 折弯之前针长外露5.6~5.7mm



CONTACTS	10	12	14	16	20	24	26
A	31.90	34.60	36.98	39.52	44.60	49.68	52.15
B	10.16	12.70	15.24	17.78	22.86	27.94	30.48
C	18.00	20.54	23.08	25.62	30.70	35.78	38.32
CONTACTS	30	34	40	50	56	60	64
A	57.40	62.38	70.00	82.70	90.32	95.40	100.48
B	35.56	40.64	48.26	60.96	68.58	73.66	78.74
C	43.40	48.48	56.10	68.80	76.42	81.50	86.58

核准:	日期:	Ckmtw 深圳市灿科盟实业有限公司 CHANKLEMENT INDUSTRYCO., LTD			
业务:	日期:	品名规格: 310SMT-2*XP			
制图: LYF	日期: 2008-07-28	单位	mm	比例	/
		图纸编号:	CKM-310-00004	版本	A

未注公差表	
X.X	±0.3
X.XX	±0.20
X.XXX	±0.100