



PC Board Side Layout
Component Side Shown

TOLERANCE TABLE	
.0	±0.20
.00	±0.10
.000	±0.05

APPROVED:	DATE:	TITLE: RJ45-8P/8C 2*1 双层 弯脚 带屏蔽 带灯 带弹片 (5JB-2X1-8P8C-LED-S-F)			
CHECKED:	DATE:	P/N			
DRAWN:	DATE:	UNIT	SCALE	Free	REV.
L. YUN	2020-05-28	mm	Free	Free	A
		FILE NO.	Ckmtw-RJ45-0237	REV.	A
				HY04	

深圳市灿科盟实业有限公司
Ckmtw CHANKLEMENT INDUSTRYCO., LTD

- NOTES:
- MATERIAL:
- 1 HOUSING MATERIAL
 - 2 CONTACT MATERIAL
 - 3 PLATING
 - 4 SHIELD
 - 5 LED
- ELECTRICAL:
- 1 VOLTAGE RATING
 - 2 CURRENT RATING
 - 3 CONTACT RESISTANCE
 - 4 INSULATION RESISTANCE
 - 5 DIELECTRIC WITHSTANDING RESISTANCE
- MECHANICAL:
- 1 DURRABILITY
 - 2 PCB RETENTION PRE-SOLDER
- ENVIRONMENTAL:
- 1 STORAGE
 - 2 OPERATION
- GLASS FILLED POLYESTER UL94V-0
PHOSPHOR BRONZE φ0.45mm
GOLD PLATING FV "50" OVER NICKEL
0.20mm THICKNESS COPPER ALLOY WITH NICKEL PLATED.
OPTION
- ±25 VAC RMS.
±15 AMP
±30 MILLIOHMS MAX.
±500 MEGOHMS MIN @ 500V DC.
±1000V AC RMS 50Hz MIN.
- ±750 CYCLES MIN.
±1 LB MIN.
- :-40°C~+85°C
: 0°C TO 70°C